SAGO





SIAE





- Constant working temperature.
- Compact and robust.
- Digital temperature display.
- Cold touch, thermal insulation.



Heated hose to get the

- Constant temperature inside the hose, automatically controlled.
- It reduces the minimum working temperature.
- It makes the system independent to the room temperature.
- It reduces the wait time; the working temperature in the spray gun is faster achieved.
- All the advantages from the SAGOLA antistatic hose, now in a heated hose.

REDUCTION

of drying times

BETTER

stretching of clearcoats

SAFE

and regular all the year

around



Easy to use; power button and temperature controller.

Out of the cabin installation

Lightweight and small; easy to locate.

Right temperature in the spray gun almost immediate

Low temperature, there is no need for gloves.

www.sagola.com
















- > P.I.D. digital temperature controller.
- > Thermocouple temperature sensor.
- > Self-learning function.
- > Overheating protection.
- > Automatic activation by flow switch.

DACK 5000X AIRHEATER



TECHNICAL DETAILS

Dimensions:

455x92x255 mm.

Weight: 3.6 Kg.

Power: 240V 50/60Hz

Max. consumption: 800w

Max. working pressure: 7 bar

Max. flow at 7 bar: 750 L

Recommended temperature:

clearcoat 40-60°C

waterborne basecoat 30-50°C

solvent based basecoat 30-40°C

Dealer's stamp



- (1) Controls
- (2) Main switch
- Red led (Heating)
- 3 Green led (Ready)
- 4 Temperature sensor
- (5) Flow meter



6 Cold air chamber, (depressurised)

1500

- 7 Hot air chamber, (pressurised)
- (8) Air inlet (from air filter)
- 9 Air outlet (hose)
- (heated hose)